

Rolamento cónico

55175-55443-TIMKEN - 55175-55443-TIMKEN

<https://www.123rolamento.pt/rolamento-mancal/rolamento-rolos/conico/55175-55443-timken>

TAPERED ROLLER BEARINGS
SINGLE-ROW • TYPE TS

TYPE TS

| Bearing Dimensions | | | Load Ratings | | | | | Part Number | |
|--------------------|---------|---------|---------------------------------------|-------------------------|---------------------------------------|-------------------------|-----------------------|-------------|-------|
| Bore d | O.D. D | Width T | Dynamic ⁽¹⁾ C ₁ | Factor ⁽²⁾ e | Dynamic ⁽¹⁾ C ₂ | Factor ⁽³⁾ K | Static C ₀ | Inner | Outer |
| mm | mm | mm | N | | N | | N | | |
| 44.450 | 112.712 | 30.162 | 129000 | 0.08 | 32700 | 49000 | 119000 | 55175 | 55443 |
| 1.7500 | 4.4375 | 1.1975 | 28500 | | 7950 | 11100 | 26700 | | |

| Bearing Dimensions | | | | | | | | | | Geometry Factors | | | Bearing Weight | |
|--------------------|---------|--------------------------|--|--------------------------------------|--|--------------------------------------|-------------------------------|-------------------------------|----------------|------------------|----------------|------|----------------|------|
| Shaft | | Housing | | Cage | | | | | G ₁ | G ₂ | C ₃ | | | |
| Width B | Width C | ER. Dr. α ⁽⁴⁾ | Max Shaft Fillet Radius R ⁽⁵⁾ | Backing Shoulder Dia. d _s | Max Housing Fillet Radius r ⁽⁶⁾ | Backing Shoulder Dia. D _s | A ₁ ⁽⁷⁾ | A ₂ ⁽⁸⁾ | | | | | | |
| 30.162 | 26.638 | 7.1 | 3.5 | 48.8 | 67.8 | 3.3 | 186.8 | 82.8 | 4.8 | 3.2 | 36.8 | 13.2 | 0.1085 | 1.38 |
| 1.1975 | 0.8725 | 0.28 | 0.14 | 2.26 | 2.84 | 0.13 | 4.17 | 2.62 | 0.18 | 0.13 | | | | 2.89 |

CARACTERÍSTICAS DO PRODUTO

| | |
|-------------------|---------------|
| Marca | TIMKEN |
| Nº Ean13 | 3663952314471 |
| Diâmetro interior | 44.45 mm |
| Diâmetro exterior | 112.712 mm |
| Espessura | 30.162 mm |
| Embalagem | 1 |

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE