

Rolamento cónico 72219C-72487-TIMKEN - 72219C-72487-TIMKEN

<https://www.123rolamento.pt/rolamento-mancal/rolamento-rolos/conico/72219c-72487-timken>

TAPERED ROLLER BEARINGS
SINGLE ROW • TYPE TS

TYPE TS

| Bearing Dimensions | | | Load Ratings | | | | | | Part Number | |
|--------------------|---------|---------|---------------------------------------|-------------------------|---------------------------------------|-------------------------|-----------------------|--------|-------------|--|
| Bore d | O.D. D | Width T | Dynamic ⁽¹⁾ C ₁ | Factor ⁽²⁾ e | Dynamic ⁽³⁾ C ₂ | Factor ⁽⁴⁾ K | Static C ₀ | Inner | Outer | |
| mm | mm | mm | N | | N | | N | | | |
| 55.562 | 123.825 | 36.512 | 214000 | 0.01 | 60000 | 20000 | 200000 | 12219C | 72487 | |
| 2.1875 | 4.8750 | 1.4375 | 48200 | | 12500 | 15800 | 49800 | | | |

| Bearing Dimensions | | | | | | | | | | Geometry Factors | | | Bearing Weight | |
|--------------------|---------|--------------------------|--|--------------------------------------|--|--------------------------------------|------------------------------------|-------------------------------|----------------|------------------|----------------|------|----------------|------|
| Width B | Width C | ER. Dr. α ⁽¹⁾ | Max Shaft Fillet Radius R ⁽²⁾ | Backing Shoulder Dia. d _s | Max Housing Fillet Radius r ⁽³⁾ | Backing Shoulder Dia. D _s | Cage A ₁ ⁽⁴⁾ | A ₂ ⁽⁵⁾ | G ₁ | G ₂ | C ₃ | | | |
| mm | mm | mm | mm | mm | mm | mm | mm | mm | | | | kg | | |
| 32.781 | 25.400 | 2.8 | 3.5 | 67.8 | 88.8 | 3.3 | 116.8 | 102.8 | 4.7 | 4.4 | 17.4 | 15.9 | 0.9025 | 2.81 |
| 1.2910 | 1.0000 | 0.08 | 0.14 | 2.64 | 3.15 | 0.13 | 4.57 | 4.02 | 0.18 | 0.18 | | | | 4.45 |

CARACTERÍSTICAS DO PRODUTO

| | |
|-------------------|---------------|
| Marca | TIMKEN |
| Nº Ean13 | 3663952317649 |
| Diâmetro interior | 55.562 mm |
| Diâmetro exterior | 123.825 mm |
| Espessura | 36.512 mm |
| Embalagem | 1 |

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE