

Rolamento cónico

95512X-95905-TIMKEN - 95512X-95905-TIMKEN

<https://www.123rolamento.pt/rolamento-mancal/rolamento-rolos/conico/95512x-95905-timken>

TAPERED ROLLER BEARINGS
SINGLE-ROW • TYPE TS

TYPE TS

| Bearing Dimensions | | | Load Ratings | | | | | | Part Number | |
|--------------------|---------|---------|---------------------------------------|-------------------------|---------------------------------------|-------------------------|-----------------------|--------|-------------|--|
| Bore d | O.D. D | Width T | Dynamic ⁽¹⁾ C ₁ | Factor ⁽²⁾ e | Dynamic ⁽³⁾ C ₂ | Factor ⁽⁴⁾ K | Static C ₀ | Inner | Outer | |
| mm | mm | mm | N | | N | | | | | |
| 130.000 | 230.000 | 63.500 | 62900 | 1.62 | 103000 | 1.58 | 97000 | 95512X | 95905 | |
| 5.1181 | 9.0501 | 2.5000 | 141000 | | 38700 | 22000 | 209000 | | | |

| Bearing Dimensions | | | | | | | | | | Geometry Factors | | | Bearing Weight | |
|--------------------|---------|--------------------------|---|---|--|---|------------------------------------|-------------------------------|-------------------------------|------------------|----------------|----------------|----------------|-------|
| Shaft | | | | | Housing | | | | | G ₁ | G ₂ | C ₃ | | |
| Width B | Width C | ER. Dr. α ⁽¹⁾ | Max Shaft Fillet Radius R ₁ ⁽²⁾ | Backing Shoulder Dia. d _s ⁽³⁾ | Max Housing Fillet Radius r ⁽⁴⁾ | Backing Shoulder Dia. D _s ⁽⁵⁾ | Cage A ₁ ⁽⁶⁾ | A ₂ ⁽⁷⁾ | A ₃ ⁽⁸⁾ | | | | | |
| mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | | | | | |
| 63.500 | 48.212 | -14.6 | 6.8 | 145.0 | 156.8 | 3.3 | 217.8 | 207.8 | 6.4 | 3.8 | 453.9 | 50.4 | 0.1203 | 10.75 |
| 2.5000 | 1.9375 | -0.58 | 0.24 | 5.71 | 6.14 | 0.13 | 8.94 | 8.15 | 0.25 | 0.15 | | | | 23.75 |

CARACTERÍSTICAS DO PRODUTO

| | |
|-------------------|---------------|
| Marca | TIMKEN |
| Nº Ean13 | 3663952325293 |
| Diâmetro interior | 130 mm |
| Diâmetro exterior | 230 mm |
| Espessura | 63.5 mm |
| Embalagem | 1 |

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE