




Rolamento esfera carreira simple ZKLN2557-2Z-INA - ZKLN2557-2Z-INA

<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/carreira-simple/zkln2557-2z-ina>

Axial angular contact ball bearings ZKLN2557-2Z
double direction, gap seals on both sides

B	25 mm	Tolerance: -0.025
D	57 mm	Tolerance: -0.010
B	28 mm	Tolerance: -0.25
	60 °	Contact angle
D_{2max}	48 mm	
d₂	40.5 mm	
d_{2min}	32 mm	
r_{1min}	0.6 mm	
r_{2min}	0.3 mm	
m	0.34 kg	Mass
C_d	27500 N	Basic dynamic load rating, axial
C_{0a}	50000 N	Basic static load rating, axial
n_{Grease}	4700 1/min	Limiting speed for grease lubrication
M_{fr}	0.2 Nm	Bearing frictional torque
S_a	750 N/mm	Axial rigidity
S_{0a}	200 1/mmrad	Tilting rigidity
M₂	0.486 kg x cm ²	Mass moment of inertia for rotating inner ring
	2 µm	Axial runout
		The axial runout data for screw drive bearing arrangements are based on the rotating inner ring.
	ZM25	Designation of recommended INA locknut
	AM25	Designation of recommended INA locknut
		Locknuts not included in delivery.
M_s	25 Nm	Tightening torque
	9410 N	Only valid in conjunction with INA precision locknuts
		Axial preload force

CARACTERÍSTICAS DO PRODUTO

Marca	INA
Nº Ean13	3663952334882
Diâmetro interior	25 mm
Impermeabilização	Placa de proteção nos dois lados
Diâmetro exterior	57 mm
Espessura	28 mm
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE