




Rolamento esfera carreira simple ZKLN4090-2Z-INA - ZKLN4090-2Z-INA

<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/carreira-simple/zkln4090-2z-ina>

Axial angular contact ball bearings ZKLN4090-2Z
Outside direction, gap seals on both sides

d	40 mm	Tolerance: -0.005
D	90 mm	Tolerance: -0.01
B	46 mm	Tolerance: -0.25
α	60 °	Contact angle
D_{1max}	80 mm	
d₁	65 mm	
d_{2min}	56 mm	
F_{1min}	0.6 mm	
F_{2min}	0.6 mm	
m	0.98 kg	Hoody weight
C₁₀	22000 N	Basic dynamic load rating, axial
C₀₂	48000 N	Basic static load rating, axial
n_{lim,grease}	3100 1/min	Limiting speed for grease lubrication
M_{fr}	0.65 Nm	Bearing frictional torque
C₁₀	1200 N/mm	Axial rigidity
C₁₀	750 N/mmrad	Tilting rigidity
M₀₂	5.5 kg x cm ²	Mass moment of inertia for rotating inner ring
r_{ax}	2.5 μm	Axial runout
		The axial runout data for screw drive bearing arrangements are based on the rotating inner ring.
	ZMA40B2	Designation of recommended INA locknut
	AMA40	Designation of recommended INA locknut
		Locknuts not included in delivery.
M_{ts}	110 Nm	Tightening torque
		Only valid in conjunction with INA precision locknuts
	25185 N	Axial preload force

CARACTERÍSTICAS DO PRODUTO

Marca	INA
Nº Ean13	3663952334936
Diâmetro interior	40 mm
Impermeabilização	Placa de proteção nos dois lados
Diâmetro exterior	90 mm
Espessura	46 mm
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE