


Rolamento esfera carreira simple ZKLN60110-2Z-INA - ZKLN60110-2Z-INA


<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/carreira-simple/zkln60110-2z-ina>

Axial angular contact ball bearings ZKLN60110-2Z
double direction, gap seals on both sides




d	60 mm	Tolerance: -0.008
D	110 mm	Tolerance: -0.015
B	45 mm	Tolerance: -0.25
α	60 °	Contact angle
D_{0max}	100 mm	
d₁	85 mm	
d₂	82 mm	
r_{1max}	0.6 mm	
r_{2max}	0.6 mm	
m	2.2 kg	Mass
C_d	84000 N	Basic dynamic load rating, axial
C_{0d}	214000 N	Basic static load rating, axial
n_{0d}	3500 1/min	Limiting speed for grease lubrication
M_{0d}	6 Nm	Bearing frictional torque
S_{0d}	1300 N/mm	Axial rigidity
C_{0d}	1500 N/mmrad	Tilting rigidity
M_{0d}	13.7 kg x cm ²	Mass moment of inertia for rotating inner ring
	3 μm	Axial runout
		The axial runout data for screw drive bearing arrangements are based on the rotating inner ring.
ZMA6098		Designation of recommended INA locknut
AM60		Designation of recommended INA locknut
		Locknuts not included in delivery.
M₀	100 Nm	Tightening torque
		Only valid in conjunction with INA precision locknuts
	17893 N	Axial preload force

Design of adjacent construction



Design of adjacent construction



Design of adjacent construction

CARACTERÍSTICAS DO PRODUTO

Marca	INA
Nº Ean13	3663952334967
Diâmetro interior	60 mm
Diâmetro interior	2.362" inch
Impermeabilização	Placa de proteção nos dois lados
Diâmetro exterior	110 mm
Diâmetro exterior	4.331" inch
Espessura	45 mm
Espessura	1.772" inch
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE