


Rolamento cónico 498-493-B-TIMKEN - 498-493-B-TIMKEN

<https://www.123rolamento.pt/rolamento-mancal/rolamento-rolos/conico/498-493-b-timken>

TAPERED ROLLER BEARINGS
TYPE TSF



| Bearing Dimensions | | | | | | | | | | Load Ratings | | | | Part Number | |
|--------------------|-----------|------------|--|-----------------------------|------|--|--|--------------------------|-------|--------------|--|--|--|-------------|--|
| Bore d | O.D. D | Width B | Dynamic ⁽¹⁾ C ₁ | Factors ⁽²⁾ e | Y | Dynamic ⁽¹⁾ C ₂ | Factors ⁽²⁾ e ₂ | Static C ₃ | Inner | Outer | | | | | |
| mm | mm | mm | N | | | N | | N | | | | | | | |
| 84.138 | 136.525 | 13.475 | 15400 | 0.14 | 1.35 | 4000 | 3000 | 21000 | 408 | 498-B | | | | | |
| 2.3175 | 5.3750 | 0.5325 | 24700 | | | 9000 | 6800 | 48000 | | | | | | | |

| Bearing Dimensions | | | | | | | | | | Shaft | | | Housing | | | Geometry Factors | | | Bearing Weight |
|--------------------|------------|-------------------------------|--|-----------------------------------|--|--|--|--|----------------|----------------|----------------|--|---------|--|--|------------------|------|----|----------------|
| Width B | Width C | Eff. Ctr. a ⁽¹⁾ | Outer Ring Range D ₁ D ₂ | Flange Width C ₁ | Max Shaft File Radius R ⁽¹⁾ | Sealing Shoulder Dia. d ₁ | Sealing Shoulder Dia. d ₂ | Sealing Shoulder Dia. D ₁ | D ₁ | D ₂ | C ₁ | | | | | | | kg | |
| mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | | | | | | | | | |
| 29.769 | 22.225 | -4.8 | 141.800 | 8.537 | 3.5 | 91.6 | 98.0 | 125.0 | 104.6 | 29.3 | 0.1202 | | | | | | 1.68 | | |
| 1.1720 | 0.8750 | -0.03 | 5.5800 | 0.2180 | 0.14 | 3.58 | 3.88 | 5.10 | | | | | | | | | 3.57 | | |

CARACTERÍSTICAS DO PRODUTO

| | |
|-------------------|---------------|
| Marca | TIMKEN |
| Nº Ean13 | 3663952339191 |
| Diâmetro interior | 84.138 mm |
| Diâmetro exterior | 136.525 mm |
| Espessura | 29.769 mm |
| Embalagem | 1 |

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE