

Casquilho de agulhas TAM1215-IKO - TAM1215-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/casquilho-agulhas/tam1215-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS




TAM TLAM

Shaft dia. mm	Identification number											
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained	Mass (Ref.) g		
12	---	---	---	---	---	---	---	---	TAM 1215	14	---	---

Boundary dimensions mm			Standard mounting dimensions mm						Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*)	Assembled inner ring	
F _w	D	C	Shaft dia. H7	Shaft dia. N7	Housing bore dia. H7	Housing bore dia. N7	Max.	Min.	N	N	rpm	IRT	
12	19	15	1.3	12.000	11.989	19.012	18.991	---	---	7 440	8 320	35 000	IRT 815

Note(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 80% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952352008
Diâmetro interior	12 mm
Diâmetro interior	0.472" inch
Diâmetro exterior	19 mm
Diâmetro exterior	0.748" inch
Espessura	15 mm
Espessura	0.591" inch
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE