

Rolamento cónico 468-452D-TIMKEN - 468-452D-TIMKEN

<https://www.123rolamento.pt/rolamento-mancal/rolamento-rolos/conico/468-452d-timken>

TAPERED ROLLER BEARINGS
DOUBLE-ROW • TYPE TDO

TYPE TDO

| Bearing Dimensions | | | | Load Ratings | | | | | | | | | |
|--------------------|---------|---------|---------------------------|------------------------|-------|-----------------------|----------------|------------------------|-------|-----------------------|-------|------|--|
| Bore d | O.D. D | Width T | Double Outer Ring Width C | Dynamic ⁽¹⁾ | | Static ⁽²⁾ | | Dynamic ⁽³⁾ | | Factor ⁽⁴⁾ | | | |
| mm | mm | mm | mm | C ₁₀ | N | Y ₁ | Y ₂ | C ₀ | N | C ₀₂ | N | K | |
| 52.387 | 107.950 | 65.090 | 53.875 | 20000 | 23000 | 0.34 | 2.01 | 3.00 | 41700 | 25000 | 72000 | 1.34 | |
| 2.9225 | 4.2500 | 2.5628 | 2.1250 | 82200 | 92200 | | | | 9270 | 5300 | 18300 | | |

| Part Number | | Dimensions | | | | | | Pin | | Geometry Factors | | | Bearing Weight |
|-------------|-------|---|--------------------------------------|---|--------------------------------------|----------------|----------------|----------------|----------------|------------------|--|------|----------------|
| Inner | Outer | Max. Shaft Fillet Radius R ₁ | Backing Shoulder Dia. d ₁ | Max. Housing Fillet Radius r ₁ | Backing Shoulder Dia. D ₁ | K ₁ | K ₂ | G ₁ | G ₂ | C ₁ | | kg | |
| 468 | 452D | 1.5 | 62.0 | 0.8 | 106.8 | - | - | 16.8 | 17.1 | 0.0940 | | 2.63 | |
| | | 0.06 | 2.44 | 0.05 | 3.84 | - | - | | | | | 5.80 | |

CARACTERÍSTICAS DO PRODUTO

| | |
|-------------------|---------------|
| Marca | TIMKEN |
| Nº Ean13 | 3663952356426 |
| Diâmetro interior | 52.387 mm |
| Diâmetro exterior | 107.95 mm |
| Espessura | 65.09 mm |
| Embalagem | 1 |

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE