


Casquilho de agulhas TAM5030-IKO - TAM5030-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/casquilho-agulhas/tam5030-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS



Shaft dia. mm	Identification number									
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained	Mass (Ref.) g
50			TAM	5030	178					

Boundary dimensions mm				Standard mounting dimensions mm						Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*)	Assembled inner ring
F _w	D	C	f ₂ Max.	Shaft dia. h8		Housing bore dia. H7		N7		N	N	rpm	IRT 4530
				Max.	Min.	Max.	Min.	Max.	Min.				
50	62	30	3.4	50.000	49.984	62.018	61.988	—	—	59 500	114 000	6 500	IRT 4530

Note(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 80% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952357461
Diâmetro interior	50 mm
Diâmetro interior	1.969" inch
Diâmetro exterior	62 mm
Diâmetro exterior	2.441" inch
Espessura	30 mm
Espessura	1.181" inch
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE