

Casquilho de agulhas YB64-IKO - YB64-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/casquilho-agulhas/yb64-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series

Shaft dia. mm (inch)	Identification number								
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained (Ref.) g
9.525 ($\frac{3}{8}$)	—	—	—	—	YB 64	3.4	—	—	—

Boundary dimensions			Standard mounting dimensions				Basic dynamic load rating	Basic static load rating	Allowable rotational speed ^(*)	Assembled inner ring
F_w	D	C	Shaft dia. h_8		Housing bore dia. J_7		C	C_0	rpm	
			Max.	Min.	Max.	Min.	N	N		
9.525 ($\frac{3}{8}$)	14.288 ($\frac{1}{2}$)	6.35 ($\frac{250}{1000}$)	9.525	9.516	14.298	14.280	4 470	5 360	16 000	—

Note^(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952361239
Diâmetro interior	9.525 mm
Diâmetro exterior	14.288 mm
Espessura	6.35 mm
Peso	3.4 g
Embalagem	1
Padrão	Nenhuma norma

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE