


## Casquilho de agulhas YB68-IKO - YB68-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/casquilho-agulhas/yb68-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**  
Inch Series



Shaft dia. mm (inch)	Identification number									
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g	
9.525 ( $\frac{3}{8}$ )	—	—	—	—	YB 68	7.2	—	—	—	—

Boundary dimensions			Standard mounting dimensions				Basic dynamic load rating		Basic static load rating		Allowable rotational speed <sup>(*)</sup>	Assembled inner ring
$F_w$	$D$	$C$	Shaft dia. h8		Housing bore dia. J7		$C$	$C_0$	$C_0$	rpm		
9.525 $\frac{1}{16}$	14.288 $\frac{1}{2}$	12.70 $\frac{1}{2}$	Max.	Min.	Max.	Min.	N	N	N	16 000	—	

Note<sup>(\*)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

## CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952361253
Diâmetro interior	9.525 mm
Diâmetro exterior	14.288 mm
Espessura	12.7 mm
Embalagem	1

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE