


## Casquilho de agulhas YBH108-IKO - YBH108-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/casquilho-agulhas/ybh108-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**  
Inch Series



Shaft dia. mm (inch)	Identification number									
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g	
15.875 ( $\frac{5}{8}$ )	—	—	—	—	—	—	—	—	YBH 108	15.3
Boundary dimensions mm(inch)		Standard mounting dimensions mm				Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(*)</sup>	Assembled inner ring	
F <sub>w</sub>	D	C	h <sub>2</sub> Shaft dia. h8 Max.	H7 Housing bore dia. Min.	N	N	rpm	IRB 68-1		
15.875 / $\frac{5}{8}$	22.225 / $\frac{7}{8}$	12.70 / 500	15.875	15.864	22.237 / 22.216	15 000	22 400	9 500	IRB 68-1	

Note<sup>(\*)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

## CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952361659
Diâmetro interior	15.875 mm
Diâmetro exterior	22.225 mm
Espessura	12.7 mm
Peso	50 g
Embalagem	1
Padrão	Nenhuma norma

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE