

Casquilho de agulhas

BHAM1616-IKO - BHAM1616-IKO

https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/casquilho-agulhas/bham1616-iko

IKO

SHELL TYPE NEEDLE ROLLER BEARINGS

Inch Series



Shaft dia. mm (inch)	Identification number			Standard		Mass (Ref.) g		Closed end		Mass (Ref.) g		Grease retained (Ref.) g	
25.400 (1)	—	—	—	—	—	—	—	—	—	—	—	—	—
Boundary dimensions mm(inch)		Standard mounting dimensions mm		Basic dynamic load rating C		Basic static load rating C ₀		Allowable rotational speed ⁽¹⁾		Assembled inner ring			
F _w	D	C	Shaft dia. h8 Max. Min.	Housing bore dia. J7 Max. Min.	N	N	rpm						
25.400	33.338	25.40(1.000)	25.400	25.387	33.352	33.327	26 400	44 500	15 000	IRB 1216			

Note⁽¹⁾

Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.

Remark

Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952362038
Diâmetro interior	25.4 mm
Diâmetro exterior	33.338 mm
Espessura	25.4 mm
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE