


Casquilho de agulhas YB2610-IKO - YB2610-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/casquilho-agulhas/yb2610-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number			Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained (Ref.) g	Mass (Ref.) g				
	Standard	Mass (Ref.) g	Closed end														
41.275 (1 5/8)	—	—	—	—	—	—	—	—	—	—	—	YB 2610	69				
Boundary dimensions		mm(inch)		Standard mounting dimensions				mm		Basic dynamic load rating		Basic static load rating		Allowable rotational speed ⁽¹⁾		Assembled inner ring	
F_w	D	C	t	Shaft dia. mm	Housing bore dia. mm	Shaft dia. inch	Housing bore dia. inch	Max.	Min.	Max.	Min.	N	N	rpm			
41.275 (1 5/8)	50.800 2	15.88 (625)	—	41.275	41.259	50.818	50.788	37 000	71 700	3 500	IRB 2210						

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952363219
Diâmetro interior	41.275 mm
Diâmetro exterior	50.8 mm
Espessura	15.88 mm
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE