


Rolamento de agulhas GBRI61812-IKO - GBRI61812-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/gbri61812-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			d	D	C	B	F_w
9.525 ($\frac{3}{8}$)	GBRI 61812	74	9.525 $\frac{+0.005}{0}$	28.575 $\frac{+0.010}{0}$	19.050 $\frac{+0.010}{0}$	19.300	15.875 $\frac{+0.010}{0}$

Standard mounting dimensions mm				Basic dynamic load C_0 (¹) N	Limiting static load rating C_0 N	Allowable rotational speed (²) rpm	Assembled inner ring LRBZ 61012
d_a Min.	d_a Max.	D_a Max.	$r_{as max}$ (¹) mm				
14	14.5	24.5	0.6	23 500	28 500	9 500	

Notes: ⁽¹⁾ Maximum permissible corner radius of the housing.
⁽²⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. No grease is preapplied. Perform proper lubrication.

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952377377
Diâmetro interior	9.525 mm
Diâmetro exterior	28.575 mm
Espessura	19.3 mm
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE