


Rolamento de agulhas GBRI122412-IKO - GBRI122412-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/gbri122412-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			d	D	C	B	F _w
19.050 (3/4)	GBRI 122412	112	19.050 ⁽¹⁾	38.100 ⁽¹⁾	19.050 ⁽¹⁾	19.300	25.400 ⁽¹⁾

Standard mounting dimensions mm		Ball angle to shaft C°	Ball race to shaft C°	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring LRBZ 121612
d _s Min. Max.	D _s Max.				
24 24.4	33.3	0.6	31 000	46 100 6 000	

Notes:⁽¹⁾ Maximum permissible corner radius of the housing.
⁽²⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks:
1. The outer ring has an oil groove and an oil hole.
2. No grease is pre-packed. Perform proper lubrication.

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952377414
Diâmetro interior	19.05 mm
Diâmetro interior	3/4" inch
Diâmetro exterior	38.1 mm
Diâmetro exterior	1 1/2" inch
Espessura	19.3 mm
Espessura	0.76" inch
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE