


Rolamento de agulhas GBRI183016-IKO - GBRI183016-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/gbri183016-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			d	D	C	B	F_w
28.575 (1 1/8)	GBRI 183016	200	28.575 (1 1/8)	47.625 (1 7/8)	25.400 (1)	25.650	34.925 (1 3/8)
Standard mounting dimensions mm		Basic dynamic load rating C_0 N	Limiting load rating C_0 N	Allowable rotational speed (1) rpm	Assembled inner ring		
d_a Min.	d_a Max.				$r_{as max}$ (1)		
33.5	33.9	42.8	0.6	49 500	91 800	4 500	LRBZ 182216

Notes: (1) Maximum permissible corner radius of the housing.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. No grease is preapplied. Perform proper lubrication.

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952377452
Diâmetro interior	28.575 mm
Diâmetro exterior	47.625 mm
Espessura	25.65 mm
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE