


Rolamento de agulhas GBRI203316-IKO - GBRI203316-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/gbri203316-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			d	D	C	B	F_w
31.750 (1 1/4)	GBRI 203316	235	31.750 (1)	52.388 (2)	25.400 (1)	25.650	38.100 (1 1/2)
Standard mounting dimensions mm		Ball diam. mm (inch)	Basic load rating C_0 N	Dynamic load rating C N	Allowable rotational speed (°) rpm	Assembled inner ring	
Min.	Max.					$r_{as\ max}$ mm	r_{in} mm
37	37.1	47.3	0.6	54 200	97 700	4 000	LRBZ 202416

Notes: (1) Maximum permissible corner radius of the housing.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. No grease is pre-packed. Perform proper lubrication.

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952377469
Diâmetro interior	31.75 mm
Diâmetro interior	1 1/4" inch
Diâmetro exterior	52.388 mm
Diâmetro exterior	2 1/16" inch
Espessura	25.65 mm
Espessura	1.01" inch
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE