


Rolamento de agulhas GBRI223516-IKO - GBRI223516-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/gbri223516-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			<i>d</i>	<i>D</i>	<i>C</i>	<i>B</i>	<i>F_w</i>
34.925 (1 3/8)	GBRI 223516	255	34.925 (1 3/8)	55.562 (2 3/16)	25.400 (1)	25.650	41.275 (1 1/2)

Standard mounting dimensions mm				Basic dynamic load rating <i>C</i> N	Static load rating <i>C₀</i> N	Allowable rotational speed (1) rpm	Assembled inner ring LRBZ 222616
<i>d_a</i> Min.	<i>d_a</i> Max.	<i>D_a</i> Max.	<i>r_{as max}</i> (°)				
40.2	40.2	50.5	0.6	56 600	105 000	3 500	LRBZ 222616

Notes: (1) Maximum permissible corner radius of the housing.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. No grease is pre-packed. Perform proper lubrication.

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952377483
Diâmetro interior	34.925 mm
Diâmetro interior	1 3/8" inch
Diâmetro exterior	55.562 mm
Diâmetro exterior	2 3/16" inch
Espessura	25.65 mm
Espessura	1.01" inch
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE