


Rolamento de agulhas GBRI223520-IKO - GBRI223520-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/gbri223520-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			d	D	C	B	F_w
34.925 (1 1/8)	GBRI 223520	316	34.925 ± 0.010	55.562 ± 0.010	31.750 ± 0.010	32.000	41.275 ± 0.010

Standard mounting dimensions mm		Basic dynamic load rating C_0	Limiting load rating C_L	Allowable rotational speed (1) rpm	Assembled inner ring LRBZ 222620		
d_a Min.	d_a Max.						
40.2	40.2	50.5	0.6	67 000	130 000	3 500	

Notes: (1) Maximum permissible corner radius of the housing.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. No grease is preapplied. Perform proper lubrication.

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952377490
Diâmetro interior	34.925 mm
Diâmetro exterior	55.562 mm
Espessura	32 mm
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE