


Rolamento de agulhas GBR364828-IKO - GBR364828-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/gbr364828-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (ref.) g	Boundary dimensions mm(inch)			Standard mounting dimensions mm (⁽¹⁾)	
			F _o	D	C	D _s Max.	r _{as} max
57.150 (2 1/4)	GBR 364828	580	57.150 (3)	76.200 (3)	44.450 (1 3/4)	69.2	1.5
Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽²⁾					
N	N	rpm					
133 000	276 000	2 500					

Notes:⁽¹⁾ Maximum permissible corner radius of the housing.
⁽²⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks:
2. The outer ring has an oil groove and an oil hole.
No grease is pre-applied. Perform proper lubrication.

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952377568
Diâmetro interior	57.15 mm
Diâmetro exterior	76.2 mm
Espessura	44.45 mm
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE