

## Rolamento de agulhas GBR405224-IKO - GBR405224-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/gbr405224-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
Without Inner Ring, Inch Series

Shaft dia. mm (inch)	Identification number	Mass (ref.) g	Boundary dimensions mm(inch)			Standard mounting dimensions mm <sup>(1)</sup>	
			F	D	C	D <sub>s</sub> Max.	r <sub>as max</sub>
<b>63.500</b> (2½)	<b>GBR 405224</b>	535	63.500 0.010	82.550 0.010	38.100 0.010	75.7	1.5
Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(2)</sup>					
N	N	rpm					
120 000	248 000	2 500					

Notes:<sup>(1)</sup> Maximum permissible corner radius of the housing.  
<sup>(2)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remarks:  
2. The outer ring has an oil groove and an oil hole.  
3. No grease is pre-applied. Perform proper lubrication.

## CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952377575
Diâmetro interior	63.5 mm
Diâmetro exterior	82.55 mm
Espessura	38.1 mm
Embalagem	1

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE