


Rolamento de agulhas GBR162412-IKO - GBR162412-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/gbr162412-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (ref.) g	Boundary dimensions mm(inch)			Standard mounting dimensions mm (1)	
			F	D	C	D _s Max.	r _{as} max
25.400 (1)	GBR 162412	79	25.400 ₀	38.100 _{±0.02}	19.050 _{±0.02}	33.3	0.6
Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽²⁾					
N	N	rpm					
31 000	46 100	6 000					

Notes: (1) Maximum permissible corner radius of the housing.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. No grease is pre-applied. Perform proper lubrication.

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952377735
Diâmetro interior	25.4 mm
Diâmetro interior	1" inch
Diâmetro exterior	38.1 mm
Diâmetro exterior	1 1/2" inch
Espessura	19.05 mm
Espessura	3/4" inch
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE