


## Rolamento de agulhas GBR202816-IKO - GBR202816-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/gbr202816-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (ref.) g	Boundary dimensions mm(inch)			Standard mounting dimensions mm <sup>(1)</sup>	
			F	D	C	D <sub>s</sub> Max.	r <sub>as</sub> max
31.750 (1 1/4)	GBR 202816	128	31.750(1 1/4)	44.450(1 3/4)	25.400(1)	39.6	0.6
Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(2)</sup>					
N	N	rpm					
46 600	83 900	4 500					

Notes:<sup>(1)</sup> Maximum permissible corner radius of the housing.  
<sup>(2)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remarks:  
1. The outer ring has an oil groove and an oil hole.  
2. No grease is pre-applied. Perform proper lubrication.

### CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952377766
Diâmetro interior	31.75 mm
Diâmetro exterior	44.45 mm
Espessura	25.4 mm
Peso	133 g
Embalagem	-
Padrão	-

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE