


Rolamento de agulhas GBR223016-IKO - GBR223016-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/gbr223016-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (ref.) g	Boundary dimensions mm(inch)			Standard mounting dimensions mm (⁽¹⁾)	
			F _o	D	C	D _s Max.	r _{as} max
34.925 (1 3/8)	GBR 223016	137	34.925(⁽¹⁾ / ₂)	47.625(1 7/8)	25.400(1)	42.8	0.6
Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed(⁽²⁾)					
N	N	rpm					
49 500	91 800	4 500					

Notes:
(⁽¹⁾) Maximum permissible corner radius of the housing.
(⁽²⁾) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks:
2. The outer ring has an oil groove and an oil hole.
No grease is pre-applied. Perform proper lubrication.

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952377773
Diâmetro interior	34.925 mm
Diâmetro exterior	47.625 mm
Espessura	25.4 mm
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE