


Rolamento de agulhas GBRI284828-IKO - GBRI284828-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/gbri284828-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			d	D	C	B	F_w
44.450 (1 1/2)	GBRI 284828	925	44.450 (1) 0	76.200 (3) 0	44.450 (1) 0	44.700	57.150 (2) 0

Standard mounting dimensions mm				Basic dynamic load rating C_0	Limiting load rating C_0	Allowable rotational speed (1) rpm	Assembled inner ring
d_a	D_a	$r_{as max}$	$r_{as max}$ (2)				
Min.	Max.	Max.	Max.	N	N		
52.5	55	69.2	1.5	133 000	276 000	2 500	LRBZ 283628

Notes: (1) Maximum permissible corner radius of the housing.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. No grease is preapplied. Perform proper lubrication.

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952377889
Diâmetro interior	44.45 mm
Diâmetro exterior	76.2 mm
Espessura	44.45 mm
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE