


## Rolamento de agulhas GBRI365624-IKO - GBRI365624-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/gbri365624-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			$d$	$D$	$C$	$B$	$F_w$
<b>57.150</b> (2 1/4)	<b>GBRI 365624</b>	955	57.150 (1) $\frac{1}{2}$	88.900 (1) $\frac{1}{2}$	38.100 (1) $\frac{1}{2}$	38.350	69.850 (1) $\frac{1}{2}$

Standard mounting dimensions mm				Basic dynamic load (kg) $C_0$	Limiting load rating $C_0$	Allowable rotational speed (2) rpm	Assembled inner ring <b>LRBZ 364424</b>
$d_a$	$D_a$	$r_{as}$	$r_{as}$ max (1)				
Min.	Max.	Max.	Max.	N	N		
65	67	82	1.5	125 000	273 000	2 000	

Notes: (1) Maximum permissible corner radius of the housing.  
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remarks: 1. The outer ring has an oil groove and an oil hole.  
2. No grease is pre-applied. Perform proper lubrication.

## CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952377919
Diâmetro interior	57.15 mm
Diâmetro exterior	88.9 mm
Espessura	38.1 mm
Embalagem	1

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE