


## Rolamento de agulhas GBRI527632-IKO - GBRI527632-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/gbri527632-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			$d$	$D$	$C$	$B$	$F_w$
<b>82.550</b> (3 1/4)	<b>GBRI 527632</b>	2 110	82.550 (3 1/4)	120.650 (4 3/4)	50.800 (2)	51.050	95.250 (3 3/4)
Standard mounting dimensions mm		Basic dynamic load rating $C_0$ N	Limiting load rating $C_0$ N	Allowable rotational speed (1) rpm	Assembled inner ring		
$d_a$ Min.	$D_a$ Max.				$r_{as max}$ (1)		
91	93	112.6	1.5	228 000	522 000	1 600	<b>LRBZ 526032</b>

Notes: (1) Maximum permissible corner radius of the housing.  
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remarks: 1. The outer ring has an oil groove and an oil hole.  
2. No grease is pre-applied. Perform proper lubrication.

## CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952377988
Diâmetro interior	82.55 mm
Diâmetro exterior	120.65 mm
Espessura	50.8 mm
Embalagem	1

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE