

Rolamento de agulhas RNA49-58-U-IKO - RNA49-58-U-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/rna49-58-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring

| Shaft dia. mm | Identification number | | | | Mass (Ref.) g | Boundary dimensions mm | | | |
|---|-----------------------|-------------------|----------------|---------------|---------------------|---------------------------|-----|-----|-----------|
| | With two seals | With one seal | With two seals | With one seal | | F_w | D | C | r_a (1) |
| 65 | — | RNA 49/58U | — | — | 275 | 65 | 82 | 25 | 1.3 |
| Standard rounding dimension D_s Max. mm | N | N | N | N | | | | | |
| Basic dynamic load rating C | 53 400 | 89 200 | 89 200 | 3 000 | | | | | |
| Basic static load rating C_0 | N | N | N | N | | | | | |
| Allowable rotational speed (reference speed) | | | | | | | | | |

Notes: (1) Minimum allowable value of chamfer dimension r .
(2) Allowable rotational speed applies to grease lubrication.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTERÍSTICAS DO PRODUTO

| | |
|-------------------|---------------|
| Marca | IKO |
| Nº Ean13 | 3663952379449 |
| Diâmetro interior | 65 mm |
| Diâmetro exterior | 82 mm |
| Espessura | 25 mm |
| Embalagem | 1 |

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE