

## Rolamento de agulhas RNA6912-U-IKO - RNA6912-U-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/rna6912-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, Without Inner Ring

Shaft dia. mm	Identification number				Mass (Ref) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		$F_w$	$D$	$C$	$r$ (1)
<b>68</b>	—	—	—	<b>RNA 6912U</b>	505	68	85	45	1
Standard mounting dimension $D_s$ Max. mm									
Basic dynamic load rating $C$									
Basic static load rating $C_0$									
Allowable rotational speed (2)									
80	93 400	186 000	3 000						

Notes: (1) Minimum allowable value of chamfer dimension  $r$ .  
(2) Allowable rotational speed applies to grease lubrication.  
Remarks: 1. The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

## CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952379494
Diâmetro interior	68 mm
Diâmetro exterior	85 mm
Espessura	45 mm
Embalagem	1

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE