

## Rolamento de agulhas RNA4928-U-IKO - RNA4928-U-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/rna4928-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, Without Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		$F_w$	$D$	$C$	$r_a$ (1)
160	—	<b>RNA 4928U</b>	—	—	2 510	160	190	50	1.5
Standard rounding dimension $D_s$ Max. mm		Basic dynamic load rating $C$ N	Basic static load rating $C_0$ N	Allowable rotational speed (grease) rpm					
182		214 000	549 000	1 200					

Notes: (1) Minimum allowable value of chamfer dimension  $r$ .  
(2) Allowable rotational speed applies to grease lubrication.  
Remarks: 1. The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

## CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952379937
Diâmetro interior	160 mm
Diâmetro interior	6.299" inch
Diâmetro exterior	190 mm
Diâmetro exterior	7.48" inch
Espessura	50 mm
Espessura	1.969" inch
Embalagem	1

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE