

Rolamento de agulhas NA6903-U-IKO - NA6903-U-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/na6903-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm				
	With two seals	With one seal	With two seals	With one seal		d	D	C	B	
17	—	—	—	—	NA 6903U	68.5	17	30	23	24

r _s min ⁽¹⁾	F _w	Standard mounting dimensions mm			Basic static load rating C ₀ N	Basic dynamic load rating C ₁₀ N	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring
		d _s Min.	d _s Max.	D _s Max.				
0.3	22	19	21	28	19 800	30 600	8 500	LRTZ 172224

Notes: (1) Minimum allowable value of shaft dimension r.
(2) Allowable rotational speed applies to grease lubrication.
Remark: This roller ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952381206
Diâmetro interior	17 mm
Diâmetro exterior	30 mm
Espessura	24 mm
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE