


## Rolamento de agulhas NA4906-U-IKO - NA4906-U-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/na4906-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring



Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
30	—	NA 4906U	—	—	106	30	47	17	18

r <sub>s</sub> mm <sup>(1)</sup>	F <sub>w</sub>	Standard mounting dimensions mm			Basic static load rating C <sub>0</sub>	Basic dynamic load rating C <sub>10</sub>	Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring
		Min.	Max.	Max.				
0.3	35	32	34	45	21 500	28 400	5 500	LRTZ 303518

Notes: (1) Minimum allowable value of chamfer dimension r.  
(2) Allowable rotational speed applies to grease lubrication.  
Remark: The outer ring has an oil groove and an oil hole.  
Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

## CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952381381
Diâmetro interior	30 mm
Diâmetro exterior	47 mm
Espessura	18 mm
Embalagem	1

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE