

Rolamento de agulhas NA69-32-U-IKO - NA69-32-U-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/na69-32-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring

Shaft dia. mm	Identification number			Mass (Ref.) g	Boundary dimensions mm				
	With two seals	With one seal	With two seals		With one seal	d	D	C	B
32	—	—	—	NA 69/32U	300	32	52	36	37

r _s min (1)	F _w	Standard mounting dimensions mm		Basic static load rating C ₀	Basic dynamic load rating C ₁₀	Allowable rotational speed(2) rpm	Assembled inner ring	
		d _s Min.	d _s Max.					D _s Max.
0.6	40	36	39	48	50 300	88 300	5 000	LRTZ 324037

Notes(1)
(1) Minimum allowable value of shaft dimension r
(2) Allowable rotational speed applies to grease lubrication.
Remark:
This roller ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952381435
Diâmetro interior	32 mm
Diâmetro exterior	52 mm
Espessura	37 mm
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE