


## Rolamento de agulhas NA6909-U-IKO - NA6909-U-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/na6909-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring



Shaft dia. mm	Identification number			Mass (Ref.) g	Boundary dimensions mm				
	With two seals	With one seal	With two seals		With one seal	d	D	C	B
45	—	—	—	NA 6909U	520	45	68	40	41

r <sub>s</sub> min <sup>(1)</sup>	F <sub>w</sub>	Standard mounting dimensions mm		Basic static load rating C <sub>0</sub>	Basic dynamic load rating C	Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring
		d <sub>s</sub> Min.	d <sub>s</sub> Max.				
0.6	52	49	51	64	66 600	127 000	LRTZ 455241

Notes: (1) Minimum allowable value of shaft dimension r  
(2) Allowable rotational speed applies to grease lubrication.  
Remark: This roller ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

## CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952381558
Diâmetro interior	45 mm
Diâmetro exterior	68 mm
Espessura	41 mm
Embalagem	1

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE