

Rolamento de agulhas NA4918-UU-IKO - NA4918-UU-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/na4918-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring

Shaft dia. mm	Identification number			Mass (Ref.) g	Boundary dimensions mm				
	With two seals	With one seal	With two seals		With one seal	d	D	C	B
90	NA 4918UU	—	—	—	1 360	90	125	35	36

r_s mm	F_w	Standard mounting dimensions mm		Basic static load rating C_0 N	Basic dynamic load rating C_1 N	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring	
		Min.	Max.					
1.1	105	96.5	103	118.5	106 000	238 000	1 800	LRTZ 9010536

Notes:
(1) Minimum allowable value of outer diameter r
(2) Allowable rotational speed applies to grease lubrication.
Remark:
1. The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952381893
Diâmetro interior	90 mm
Diâmetro exterior	125 mm
Espessura	36 mm
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE