

Rolamento de agulhas NA4928-UU-IKO - NA4928-UU-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/na4928-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
140	NA 4928UU	—	—	—	4 340	140	190	50	51

r_s min (1)	F_w	Standard mounting dimensions mm		Basic static load rating C_0	Basic dynamic load rating C_1	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring LRTZ 14016051
		Min.	Max.				
1.5	160	148	158	214 000	549 000	1 200	

Notes:
(1) Minimum allowable value of chamfer dimension r
(2) Allowable rotational speed applies to grease lubrication.
Remark:
1. This outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952382050
Diâmetro interior	140 mm
Diâmetro exterior	190 mm
Espessura	51 mm
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE