

Rolamento de agulhas BR142216-U-IKO - BR142216-U-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/br142216-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		F_w	D	C
22.225 ($\frac{7}{8}$)		BR 142216 U	76	22.225 ($\frac{7}{8}$)	34.925 (1 $\frac{3}{8}$)	25.400 (1)
Standard mounting dimensions mm		Basic dynamic load rating C	Basic static load rating C_0	Allowable rotational speed ^(*)		
D_1 Max.	F_{is} max (^(†))	N	N	rpm		
29.7	1.0	21 600	26 900	9 000		

Notes: (*) Minimum allowable value of diameter dimension r
(†) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952382135
Diâmetro interior	22.225 mm
Diâmetro interior	7/8" inch
Diâmetro exterior	34.925 mm
Diâmetro exterior	1 3/8" inch
Espessura	25.4 mm
Espessura	1" inch
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE