

Rolamento de agulhas BR263520-U-IKO - BR263520-U-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/br263520-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring

Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		F_w	D	C
41.275 (1 5/8)		BR 263520 U	179	41.275 (1 5/8)	55.562 (2 1/8)	31.750 (1 1/4)
Standard mounting dimensions mm		Basic dynamic load rating	Static load rating	Allowable rotational speed ⁽²⁾		
D_1	$r_{as\ max}$ ⁽¹⁾	C	C_0	rpm		
Max.		N	N			
48.3	1.5	44 800	70 900	4 500		

Notes: (1) Minimum allowable value of chamfer dimension r .
(2) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952382258
Diâmetro interior	41.275 mm
Diâmetro exterior	55.562 mm
Espessura	31.75 mm
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE