


Rolamento de agulhas BRI82016-UU-IKO - BRI82016-UU-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/bri82016-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring, Inch Series



| Shaft dia. mm (inch) | Identification number | | Mass (Ref.) g | Boundary dimensions mm(inch) | | | | |
|----------------------------|-----------------------------------|---------------|-------------------------------------|--|--|----------------------|--------|---------------------|
| | With two seals | With one seal | | d | D | C | B | |
| 12.700 (.50) | BRI 82016 UU | | 99 | 12.700 (.50) | 31.750 (1.25) | 25.400 (1.0) | 25.650 | |
| F_w | Standard mounting dimensions (mm) | | Basic dynamic load rating C N | Basic static load rating C_0 N | Allowable rotational speed ⁽²⁾ rpm | Assembled inner ring | | |
| | Min. | Max. | | | | Min. | Max. | |
| 19.050 (.75) | 17.5 | 18 | 26.5 | 0.6 | 20 700 | 24 400 | 10 000 | LRBZ 81216 B |

Notes: (1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTERÍSTICAS DO PRODUTO

| | |
|-------------------|---------------|
| Marca | IKO |
| Nº Ean13 | 3663952382494 |
| Diâmetro interior | 12.7 mm |
| Diâmetro exterior | 31.75 mm |
| Espessura | 25.4 mm |
| Embalagem | 1 |

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE