

Rolamento de agulhas BRI102216-UU-IKO - BRI102216-UU-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/bri102216-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring, Inch Series

| Shaft dia. mm (inch) | Identification number | | Mass (Ref.) g | Boundary dimensions mm(inch) | | | | |
|------------------------------------|-----------------------------------|---------------|---------------------|---------------------------------------|--|--|---------------------------------------|--|
| | With two seals | With one seal | | d | D | C | B | |
| 15.875 ($\frac{3}{4}$) | BRI 102216 UU | | 113.5 | 15.875 ($\frac{3}{4}$) | 34.925 (1 $\frac{3}{4}$) | 25.400 (1) | 25.650 | |
| F_w | Standard mounting dimensions (mm) | | | Basic dynamic load rating C N | Basic static load rating C_0 N | Allowable rotational speed ⁽²⁾ rpm | Assembled inner ring LRBZ 101416 B | |
| | Min. | Max. | Max. | | | | | |
| 22.225 ($\frac{7}{8}$) | 21 | 21.2 | 29.7 | 21 600 | 26 900 | 9 000 | | |

Notes:
(1) Minimum allowable value of chamfer dimension r
(2) Allowable rotational speed applies to grease lubrication.
Remark:
1. The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTERÍSTICAS DO PRODUTO

| | |
|-------------------|---------------|
| Marca | IKO |
| Nº Ean13 | 3663952382500 |
| Diâmetro interior | 15.875 mm |
| Diâmetro exterior | 34.925 mm |
| Espessura | 25.4 mm |
| Embalagem | 1 |

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE