

## Rolamento de agulhas BRI102216-U-IKO - BRI102216-U-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/bri102216-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring, Inch Series

Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)				
	With two seals	With one seal		d	D	C	B	
<b>15.875</b> ( $\frac{3}{4}$ )		<b>BRI 102216 U</b>	113.5	15.875 ( $\frac{3}{4}$ )	34.925 (1 $\frac{3}{4}$ )	25.400 (1 )	25.650	
$F_w$	Standard mounting dimensions (mm)			Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N	Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring LRBZ 101416 B	
	Min.	Max.	Max. as max. <sup>(1)</sup>					
<b>22.225</b> ( $\frac{7}{8}$ )	21	21.2	29.7	0.6	21 600	26 900	9 000	

Notes: (1) Minimum allowable value of chamfer dimension r.  
(2) Allowable rotational speed applies to grease lubrication.  
Remark: The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952382517
Diâmetro interior	15.875 mm
Diâmetro exterior	34.925 mm
Espessura	25.4 mm
Peso	150 g
Embalagem	-
Padrão	-

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE