

Rolamento de agulhas BRI203320-UU-IKO - BRI203320-UU-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/bri203320-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring, Inch Series

Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)			
	With two seals	With one seal		d	D	C	B
31.750 (1 1/4)	BRI 203320 UU		254	31.750 (1 1/4)	52.388 (2 1/8)	31.750 (1 1/4)	32.000
F_w	Standard mounting dimensions (mm)			Basic dynamic load rating C N	Basic static load rating C ₀ N	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring
	Min.	Max.	Misg. as max. ⁽¹⁾				
38.100 (1 1/2)	37	37.1	45.1	43 700	66 900	5 500	LRBZ 202420 B

Notes: (1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to grease lubrication.
Remark: This roller ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952382616
Diâmetro interior	31.75 mm
Diâmetro exterior	52.388 mm
Espessura	31.75 mm
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE