

## Rolamento de agulhas BRI243920-UU-IKO - BRI243920-UU-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/bri243920-uu-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring, Inch Series

Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)			
	With two seals	With one seal		d	D	C	B
<b>38.100</b> (1 1/2)	<b>BRI 243920 UU</b>		<b>362</b>	<b>38.100</b> (1 1/2)	<b>61.912</b> (2 3/8)	<b>31.750</b> (1 1/4)	<b>32.000</b>
$F_w$	Standard mounting dimensions (mm)			Basic dynamic load rating $C$ N	Basic static load rating $C_0$ N	Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring
	Min.	Max.	Mfg. as max. <sup>(1)</sup>				
<b>47.625</b> (1 7/8)	<b>43.3</b>	<b>45</b>	<b>54.7</b>	<b>48 500</b>	<b>82 100</b>	<b>4 000</b>	<b>LRBZ 243020 B</b>

Notes: (1) Minimum allowable value of chamfer dimension r.  
(2) Allowable rotational speed applies to grease lubrication.  
Remark: This outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

## CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952382661
Diâmetro interior	38.1 mm
Diâmetro exterior	61.912 mm
Espessura	31.75 mm
Embalagem	1

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE