


Rolamento de agulhas BRI325228-UU-IKO - BRI325228-UU-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/bri325228-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)				
	With two seals	With one seal		d	D	C	B	
50.800 (2)	BRI 325228 UU		889	50.800 (2)	82.550 (3 1/4)	44.450 (1 3/4)	44.700	
F _w	Standard mounting dimensions (mm)		Basic dynamic load rating C N	Basic static load rating C ₀ N	Allowable rotational speed ^(*) rpm	Assembled inner ring		
	Min.	Max.				Misg.	r	r ₁
63.500 (2 1/2)	58	61	74.3	1.5	94 600	174 000	3 000	LRBZ 324028 B

Notes: (*) Minimum allowable value of chamfer dimension r
(**) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952382739
Diâmetro interior	50.8 mm
Diâmetro exterior	82.55 mm
Espessura	44.45 mm
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE