

Rolamento de agulhas BRI406028-UU-IKO - BRI406028-UU-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/bri406028-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring, Inch Series

Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)			
	With two seals	With one seal		d	D	C	B
63.500 (2 1/2)	BRI 406028 UU		1 065	63.500 (2 1/2)	95.250 (3 7/8)	44.450 (1 3/4)	44.700

F _w	Standard mounting dimensions (mm)			Basic dynamic load rating C N	Basic static load rating C ₀ N	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring LRBZ 404828 B
	d _s Min.	d _s Max.	D _s Max. as max. ⁽¹⁾				
76.200 (3)	71	73	87.0	105 000	211 000	2 500	

Notes: (1) Minimum allowable value of chamfer dimension r
(2) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952382777
Diâmetro interior	63.5 mm
Diâmetro exterior	95.25 mm
Espessura	44.45 mm
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE