


Rolamento de agulhas GBR182620-U-IKO - GBR182620-U-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/gbr182620-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		F_w	D	C
28.575 (1.125)	GBR 182620 UU		139	28.575 (1.125)	41.275 (1.625)	31.750 (1.250)
Standard mounting dimensions mm		Ball dynamic load rating C	Ball static load rating C_0	Allowable rotational speed ^(*)		
D_s Max.	r as max (^(†))	N	N	rpm		
36.3	0.6	43 900	75 300	3 000		

Notes: (*) Minimum allowable value of diameter dimension r
(†) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952382937
Diâmetro interior	28.575 mm
Diâmetro exterior	41.275 mm
Espessura	31.75 mm
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE