


Rolamento de agulhas GBR223020-UU-IKO - GBR223020-UU-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/gbr223020-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		F_w	D	C
34.925 (1.375)	GBR 223020 UU		183	34.925 (1.375)	47.625 (1.875)	31.750 (1.250)
Standard mounting dimensions mm		Seal dynamic load rating C	Ball static load rating C_0	Allowable rotational speed ^(*)		
D_A Max.	r as max (°)	N	N	rpm		
42.8	0.6	49 500	91 800	2 500		

Notes: (*) Minimum allowable value of chamfer dimension r .
(**) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952382968
Diâmetro interior	34.925 mm
Diâmetro exterior	47.625 mm
Espessura	31.75 mm
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE