


Rolamento de agulhas GBR567232-UU-IKO - GBR567232-UU-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/gbr567232-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.1) g	Boundary dimensions mm(inch)		
	With two seals	With 6/8e seal		F_w	D	C
88.900 (3 1/2)	GBR 567232 UU		1 240	88.900 (3 1/2)	114.300 (4 1/2)	50.800 (2)
Standard mounting dimensions mm		Seal dynamic load rating C	Ball static load rating C_0	Allowable rotational speed ⁽²⁾		
D_A Max.	r as max (°)	N	N	rpm		
106.3	1.5	170 000	347 000	900		

Notes: (1) Minimum allowable value of chamfer dimension r .
(2) Allowable rotational speed applies to grease lubrication.
Remark: This roller ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952383200
Diâmetro interior	88.9 mm
Diâmetro exterior	114.3 mm
Espessura	50.8 mm
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE